# 4G300

## WiFi Anywhere, Anytime

### Compatible with 4G/3G mobile broadband modems
### Internal 2600mAh battery

**Wireless N300 3G/4G Router**

The Tenda 4G300 Wireless N300 3G/4G Router is specially designed for mobility. The device is compatible with 4G and 3G networks. By plugging an activated FDD-LTE/TD-LTE/HSPA+/HSPA/HSDPA/EVDO modem, and it turns 4G/3G signal into a high speed WiFi Hotspot with data rate of up to 300Mbps. Whether you're on the road, at airport, or camping, you can always instantly set up a WiFi hotspot and share by your companions. It provides an Ethernet port, so that you can connect it to an existing wired network using an Ethernet cable and enjoy Internet activities like surfing, chatting, and streaming video wirelessly. In addition, for increased mobility, the device is built with an internal battery with a capacity of 2600mAH. It gives you freedom to roam anywhere anytime. Ideal for people who are on the go.

## Easy 3G/4G Sharing

By inserting an activated TD-LTE/FDD-LTE USB modem, this 802.11n compliant router gives you freedom to roam and still remain connected to the Internet. It is also backward compatible with 3G networks including WCDMA and CDMA 2000.

## Mobile Power Bank

The device is designed with internal lithium ion battery and dual USB ports that can charge to your smartphones or tablets while working. With a capacity of 2600mAh, it is good for up to 8 hours regular Internet activities.

## Make Wired Wireless

Plug an Ethernet cable into the device and connect it to your exisisting wired network, it turns the wired connection into a WiFi hotspot, so that your smartphone, laptop, or tablet can access to Internet and share wirelessly and simultaneously.

## Specifications

| | | |
|---|---|---|
| Hardware Specification | Protocol Standard | IEEE 802.11b,IEEE 802.11g,IEEE 802.11n,IEEE 802.3u |
| | Port | 1*RJ-45<br>1*USB 2.0<br>1*Micro USB |
| | Antenna | 2* Internal Antenna |
| | Button | Switch Button<br>Reset Button |
| | Power Source | Input：(VAC ) 100-240V；50Hz<br>Output：(VDC) 5V，1.2A |
| | Capacity | 2600mAh |
| | Product Size ( L*W*H ) | 89.9mm*41.6mm*38.9mm |
| | LED Indicator | 1* Capacity LED Indicator |
| Wireless Parameter | Wireless Network Rate | 300Mbps |
| | Frequency | 2.4GHz |
| | Basic Function | Modify network model,SSID,Broadcast,Channel,Channel Bandwidth |
| | Wireless Security | Support WPA-PSK,WPA2-PSK,WPA&WPA2-PSK mixed and a series of encryption and security |
| Software Features | WAN Accessing Method | 3G/4G,PPPOE,DHCP,Static |
| | Operating Mode | Family,Hotel,3G/4G,WISP |
| | DHCP Configuration | DHCP Server<br>Client List<br>Static Address Assignment |
| | Virtual Server | Port Transmit |
| | Security Configuration | Client Filter |
| | VPN Penetration | Support |
| | DDNS | 88ip.cn/3322.org/no-ip.com/DynDNS.com |
| Additional Information | Temperature | Operating Temperature：-10℃ to 40℃；<br>Storage Temperature：-40℃to 70 |
| | Humidity | Operating Humidity：10% to 90%RH Non-condensing<br>Storage Humidity：5% to 90%RH Non-condensing |
| | Default Settings | SSID:Tenda+ the last six numbers of MAC address<br>Wireless Network Password: None<br>Default Access Mode: DHCP |
| | Certification | FCC/CE/RoHS/WEEE |
| | Associated Products | 4G301,4G302,3G189E,3G-W6 |
| | Packing Accessories | 4G300*1<br>Quick Installation Guide*1<br>Network Cable*1<br>USB Cable*1<br>Warranty Card*1 |

SHENZHEN TENDA TECHNOLOGY CO.,LTD.
No. 34-1 Shilong Road Shiyan Town, Baoan District Shenzhen 518108,China
Phone: (86 755) 2765 7180 Fax:(86 755) 2765 7178
Email: sales@tenda.com.cn support@tenda.com.cn
http://www.tendacn.com

©2013 SHENZHEN TENDA TECHNOLOGY CO.,Ltd, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co.,Ltd in China and/or other countries. Other Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.